参考資料1. 型式口径別トルクレンチ・六角棒ソケット組み合わせ一覧 QL100N4-MH QL280N-MH QL25N-MH QL50N-MH トルクレンチ QL200N4-MH 20~100 40~280 調整範囲(N·m) 5~25 10~50 40~200 型式 角ドライブ(mm) 9.5 × 9.5× 12.7× 12.7 × 12.7× 六角棒サイズ(mm) 5 8 10 5 6 8 10 6 8 | 10 | 12 | 14 | 8 10 | 12 | 14 | 17 12 | 14 | 17 6 G-20 • 25 G-32 • 40 0 0 0 G-50 0 注O G-65-80-100 0 0 Gタイプ G-125-150 0 0 G-200 0 0 G-250 0 0 G-300 - 350 - 400 Ο GD-80 0 0 0 GDタイプ GD-100 0 0 GU-20 0 GU-25 - 32 0 GU-40 0 0 GUタイプ GU-50 0 0 GU-65 0 0 GU-80 - 100 0 0 0 GVPP-20-25 0 GVPプラス GVPP-30 0 0 316-20-25 0 316-32-40 0 0 316-50-65-80 0 0 316タイプ 0 0 316-100 316-125-150 Ο 0 \circ 316-200 0 0 GT-50 0 0 注Ο GTタイプ GT-65-80-100 0 0 GT-125 • 150 0 0 CT-50 0 Ο CTタイプ CT-65-80-100 0 0 F-50 0 F-65-80-100 0 0 Fタイプ F-125-150 0 0 0 F-175~400 0 F-450 - 500 - 600 0 FVU-350E 0

● (注)はステンレスボルト仕様時です。クロモリボルト仕様時はこのトルクレンチ及びソケットは使用できません。

FVUタイプ

FVU-400E

● 標準トルク値は、性能・品質改善の為、予告なく変更する場合がございます。必ず製品ラベルをご確認ください。

0

参考資料2.

型式口径別トルクレンチ・六角棒ソケット組み合わせ一覧

	トルクレンチ	QL25N-MH				QL50N-MH				QL100N4-MH					QL200N4-MH					012	280N-	 -МН
型式	調整範囲(N·m)	5~25				10~50				20~100					40~200				QL280N-MH 40~280			
	角ドライブ(mm)	5~25 9.5 ×				9.5 ×				20~100 12.7×					40~200 12.7×					12.7 ×		
	六角棒サイズ(mm)					5 6 8 10				6 8 10 12 14				8 10 12 14 17				12 14 17				
	FC-80A	0	0	0	10	0	0		10			10	12	17		10	12	17	17	12	14	17
FCタイプ	FC-100A-125A		0			\vdash	0			0												
	FC-150A							0			0				0							
FCVタイプ	FCV-80A	0				0																
	FCV-100A-125A		0			Ť	0			0												
	FCV-150A						_	0			0				0							
Cタイプ	C-50		0				0								_							
	C-65-80-100		0				0															
	C-125•150			0				0			0											
	C-200~400													0								
	C-450-500-600													0								
	C-700													0				0				
CSタイプ	CS-40	0																				
	CS-50-65		0				0															
	CS-80-100			0				0			0											
	CS-125-150								0			0										
	CS-200								0			0				0						
	CS-250											0				0						
	CS-300												0				0					
CULタイプ	CUL-20E • 25E	0																				
	CUL-32E • 40E		0																			
	PPSK- 50 I								0			0				0						
	PPSK- 75 I								0			0				0						
	PPSK-100 I																	0			0	
プラストプロ	PPAD- 50 I								0			0				0						
JWWA K 144	PPAD- 75 I								0			0				0						
	PPAD-100 I																	0			0	
ISOサイズ	PPWP- 50 I								0			0				0						
	PPWP- 75 I											0				0						
	PPWP-100 I																	0			0	
	PPWP-150 I																	0			0	
	PPSK- 50 J								0			0				0						
	PPSK- 75 J											0				0						
	PPSK-100 J																	0			0	
プラストプロ	PPAD- 50 J								0			0				0						
PWA 001	PPAD- 75 J											0				0					_	
	PPAD-100 J																	0			0	
JISサイズ	PPWP- 50 J								0			0				0						
	PPWP- 75 J											0				0						
	PPWP-100 J																	0			0	
	PPWP-150 J																	0			0	

[●] 標準トルク値は、性能・品質改善の為、予告なく変更する場合がございます。必ず製品ラベルをご確認ください。