

参考資料1.

型式口径別トルクレンチ・六角棒ソケット組み合わせ一覧

型式	トルクレンチ	QL25N-MH				QL50N-MH				QL100N4-MH					QL200N4-MH					QL280N-MH		
	調整範囲(N・m)	5～25				10～50				20～100					40～200					40～280		
	角ドライブ(mm)	9.5 ×				9.5 ×				12.7 ×					12.7 ×					12.7 ×		
	六角棒サイズ(mm)	5	6	8	10	5	6	8	10	6	8	10	12	14	8	10	12	14	17	12	14	17
Gタイプ	G-20・25	○																				
	G-32・40		○				○															
	G-50		○				○			注○												
	G-65・80・100							○			○											
	G-125・150												○				○					
	G-200																	○			○	
	G-250																		○			○
	G-300・350・400																					○
GDタイプ	GD-80								○			○				○						
	GD-100											○				○						
GUタイプ	GU-20	○																				
	GU-25・32	○																				
	GU-40		○				○															
	GU-50			○				○														
	GU-65			○				○														
	GU-80・100								○			○				○						
GVPプラス	GVPP-20・25	○																				
	GVPP-30		○				○															
316タイプ	316-20・25	○																				
	316-32・40		○				○															
	316-50・65・80		○				○															
	316-100		○				○															
	316-125・150							○			○				○							
	316-200											○				○						
GTタイプ	GT-50		○				○			注○												
	GT-65・80・100							○			○											
	GT-125・150												○				○					
CTタイプ	CT-50		○				○															
	CT-65・80・100		○				○															
Fタイプ	F-50		○																			
	F-65・80・100			○				○														
	F-125・150				○				○			○										
	F-175～400													○								
	F-450・500・600													○								
FVUタイプ	FVU-350E												○									
	FVU-400E												○									

- (注)はステンレスボルト仕様時です。クロモリボルト仕様時はこのトルクレンチ及びソケットは使用できません。
- 標準トルク値は、性能・品質改善の為、予告なく変更する場合がございます。必ず製品ラベルをご確認ください。

参考資料2.

型式口径別トルクレンチ・六角棒ソケット組み合わせ一覧

型式	トルクレンチ	QL25N-MH				QL50N-MH				QL100N4-MH					QL200N4-MH					QL280N-MH			
	調整範囲(N・m)	5～25				10～50				20～100					40～200					40～280			
	角ドライブ(mm)	9.5×				9.5×				12.7×					12.7×					12.7×			
	六角棒サイズ(mm)	5	6	8	10	5	6	8	10	6	8	10	12	14	8	10	12	14	17	12	14	17	
FCタイプ	FC-80A	○				○																	
	FC-100A・125A		○				○			○													
	FC-150A							○			○				○								
FCVタイプ	FCV-80A	○				○																	
	FCV-100A・125A		○				○			○													
	FCV-150A							○			○				○								
Cタイプ	C-50		○				○																
	C-65・80・100		○				○																
	C-125・150			○				○			○												
	C-200～400													○									
	C-450・500・600													○									
	C-700													○				○					
CSタイプ	CS-40	○																					
	CS-50・65		○				○																
	CS-80・100			○				○			○												
	CS-125・150								○			○											
	CS-200								○			○				○							
	CS-250											○				○							
	CS-300												○				○						
CULタイプ	CUL-20E・25E	○																					
	CUL-32E・40E		○																				
JWWA K 144 ISOサイズ	PPSK- 50 I								○			○				○							
	PPSK- 75 I								○			○				○							
	PPSK-100 I																○				○		
	PPAD- 50 I								○			○				○							
	PPAD- 75 I								○			○				○							
	PPAD-100 I																○				○		
	PPWP- 50 I								○			○				○							
	PPWP- 75 I											○				○							
	PPWP-100 I																	○			○		
	PPWP-150 I																	○			○		
PWA 001 JISサイズ	PPSK- 50 J								○			○				○							
	PPSK- 75 J											○				○							
	PPSK-100 J																○				○		
	PPAD- 50 J								○			○				○							
	PPAD- 75 J											○				○							
	PPAD-100 J																	○			○		
	PPWP- 50 J								○			○				○							
	PPWP- 75 J											○				○							
	PPWP-100 J																	○			○		
	PPWP-150 J																	○			○		

● 標準トルク値は、性能・品質改善の為、予告なく変更する場合がございます。必ず製品ラベルをご確認ください。